

SSB

Automotive SILVER



"Unlike many who claim to have a maintenance-free battery, the SSB Automotive line is a Genuine Maintenance-Free in every respect. SSB Automotive batteries are filled and heat sealed at the factory so that you simply install this battery and virtually forget about it"

- **High Performance Maintenance Free - Non-Spillable**
- **Powerful Cranking Power**
- **Higher Reserve Capacity**
- **Calcium Calcium Design**
- **Long Life Grid Design - Genuine Expanded Grid**
- **Design & Built Tough for Australian Conditions**
- **Good Cycle Life**
- **Flame Arrestors - To prevent sparks entering the battery for added safety**
- **Superior Design & Quality - Manufactured to Quality Assurance Standard ISO 9001**
- **When Failure is not an Option - Use only SSB Automotive Batteries**



**Designed For
Australian Conditions**



**Higher
Cranking Capacity**



**Higher
Reserve Capacity**



**Long Life
Design**



**Maintenance
Free**

QUALITY ASSURANCE
ISO 9001

www.superstart.com.au



25 YEARS
EXPERIENCE



Specifications

MODEL	VOLTS	CCA	RESERVE CAPACITY (mins)	DIMENSIONS				ASSEMBLY FIGURE	TERMINAL TYPE	WEIGHT (KG)
				LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)	TERMINAL HEIGHT (mm)			
ES50P	12	570	120	236	170	187	208	+ -	STD SAE	12.37
ES50PL	12	570	120	236	170	187	211	- +	STD SAE	12.37
ES40Z/ZA	12	350	70	195	127	200	221	+ -	DUAL POST	9.37
ES40ZL/ZAL	12	350	70	195	127	200	221	- +	DUAL POST	9.19
ES40T/60	12	450	90	236	127	200	221	+ -	DUAL POST	11.67
ES40TL/60L	12	450	90	236	127	200	221	- +	DUAL POST	11.38
ES55D23L	12	570	130	230	170	200	221	- +	STD SAE	12.78
ES55D23R	12	570	130	230	171	200	221	+ -	STD SAE	12.78
ES55	12	550	120	242	174	174	174	+ -	STD SAE	11.77
ES55T	12	570	130	236	170	187	208	- +	STD SAE	15.19
ES66	12	670	150	276	174	174	174	+ -	STD SAE	14.21
ES66T	12	700	160	274	174	190	190	- +	STD SAE	16.98
ES75	12	780	170	310	174	173	173	- +	STD SAE	17.68
ES75T	12	800	190	310	173	189	189	+ -	STD SAE	18.95
ES88	12	840	190	353	175	173	173	- +	STD SAE	19.94
ES88T	12	890	210	353	174	190	190	- +	STD SAE	22.14
ES70	12	670	160	267	175	200	221	+ -	STD SAE	14.37
ES70L	12	670	160	267	175	200	221	- +	STD SAE	14.93
ES70ZZ	12	760	190	303	170	201	222	+ -	STD SAE	17.53
ES70ZZL	12	760	190	303	170	201	222	- +	STD SAE	17.15
ES86X	12	1000	260	329	171	215	237	+ -	STD SAE	25.00
ESN94	12	1050	350	503	213	191	211	- +	STD SAE	39.00
ESN100	12	880	210	503	213	191	211	+ -	STD SAE	37.00
ESN100L	12	880	210	503	231	191	211	- +	STD SAE	37.00
ESN120	12	1000	270	513	181	222	243	+ -	STD SAE	34.50
ESN150	12	1100	330	513	222	223	244	- +	STD SAE	40.00
ESN200	12	1300	450	509	265	230	250	+ -	STD SAE	53.50



QUALITY ASSURANCE
ISO 9001

www.superstart.com.au

