











AGM Start-stop Auxiliary Battery

- Ultra High Performance
- Advanced AGM Battery IOO% Leak-Proof and Spill-proof *SS-AU35 excluded
- Lastest OE Technology for the latest Hi-Tech Start-Stop Vehicles
- Powerful Cranking Power even with a low state of charge
- Long Life Grid Design Has up to 4 times the Cycle Life of flooded MF car batteries
- Extreme Vibration Resistant
- Perfect for High End Luxury and High Performance Vehicles
- Superior Design & Quality Manufactured to Quality Assurance Standard ISO 9001
- Rated for Under Bonnet use
- Exempt from Dangerous Goods Classification
- When Failure is not an Option Use only SSB i-Start Batteries



Designed For Australian Conditions



Long Life Design



Vibration Resistant



Deep Cycle



Maintenance Free

MODEL	VOLTS	CCA	RC (mins)	AH (20HR)	DIMENSIONS					TEDMINAL	WEIGHT
					LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)	TERMINAL HEIGHT (mm)	ASSEMBLY FIGURE	TERMINAL TYPE	WEIGHT (KG)
SS-CX23	12	380	-	14	150	87	145	145	+ -	JIS / Thin Post	4.74
SS-VV12	12	170	-	12	150	87	130	130	+ -	ML	4.25
SS-BW14	12	200	-	12	150	87	145	145	+ -	ML	4.76
SS-MB14	12	200	-	12	150	87	145	145	+ -	OEM	4.76
SS-AUX35 Non-AGM TECH	12	520	-	35	207	175	140	140	_ +	STD	10.30



